




COMFORT 1



Asymmetric pattern shape, optimized variable pitch pattern design, provide quiet ride environment.



Nice driving pleasure comes from strong tread and soft sidewall.



Perfect handling performance and good cornering performance.



Silica tread compound for low rolling resistance and good wet grip.

Series	Size	Load Index	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Max. Pressure	
					mm	mm	kg	lbs	kPa	psi
55	185/55R14	80	H/V	6.0	194	560	450	992	300	44
	185/55R15	82	H/V	6.0	194	585	475	1047	300	44
	195/55R15	85	H/V	6.0	201	595	515	1135	300	44
	195/55R16	87	H/V	6.0	201	620	545	1201	300	44
	205/55R16	91	H/V	6.5	214	632	615	1356	300	44
	215/55R16	93	H/V	7.0	226	642	650	1433	300	44
60	175/60R13	77	H/V	5.0	177	540	412	908	300	44
	185/60R14	82	H/V	5.5	189	578	475	1047	300	44
	185/60R15	84	H/V	5.5	189	603	500	1102	300	44
	195/60R14	86	H/V	6.0	201	590	530	1168	300	44
	195/60R15	88	H/V	6.0	201	615	560	1235	300	44
	205/60R15	91	H/V	6.0	209	627	615	1356	300	44
	205/60R16	92	H/V	6.0	209	652	630	1389	300	44
	215/60R15	94	H/V	6.5	221	639	670	1477	300	44
	215/60R16	95	H/V	6.5	221	664	690	1521	300	44
	225/60R16	98	H/V	6.5	228	676	750	1653	300	44
	235/60R16	100	H/V	7.0	240	688	800	1764	300	44


CATCHGRE GP¹⁰⁰


ECONOMIC & ORDINARY



Four circumferential tread grooves, excellent water drainage, improving wet handling.



Continuous and wide shoulder block design maintains the stability at cornering and brings precise driving experience.



Special grooves design to bring the superior quiet effect.



Special wear-resisting tread compound to provide excellent trip mileage.

Series	Size	Load Index	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Max. Pressure	
					mm	mm	kg	lbs	kPa	psi
65	165/65R13	77	T	5.0	170	544	412	908	300	44
	165/65R14	79	T	5.0	170	570	437	963	300	44
	175/65R14	82	T/H	5.0	177	584	475	1047	300	44
	185/65R14	86	T/H	5.5	189	596	530	1168	300	44
	185/65R15	88	T/H	5.5	189	621	560	1235	300	44
	195/65R14	89	T/H	6.0	201	610	580	1279	300	44
	195/65R15	91	T/H	6.0	201	635	615	1356	300	44
	205/65R15	94	T/H	6.0	209	647	670	1477	300	44
	215/65R15	96	T/H	6.5	221	661	710	1565	300	44
	155/70R13	75	T	4.5	157	548	387	853	300	44
70	165/70R13	79	T	5.0	170	562	437	963	300	44
	165/70R14	81	T	5.0	170	588	462	1019	300	44
	175/70R13	82	T	5.0	177	576	475	1047	300	44
	175/70R14	84	T	5.0	177	602	500	1102	300	44
	185/70R13	86	T/H	5.5	189	590	530	1168	300	44
	185/70R14	88	T/H	5.5	189	616	560	1235	300	44
	195/70R14	95 XL	T/H	6.0	201	630	690	1521	340	50
	205/70R14	98 XL	T/H	6.0	209	644	750	1653	340	50
	205/70R15	96	T/H	6.0	209	669	710	1565	300	44
	215/70R15	98	T/H	6.5	221	683	750	1653	300	44
80	225/70R15	100	T/H	6.5	228	697	800	1764	300	44
	155/80R13	79	T	4.5	157	578	437	963	300	44



CATCHPOWER



Four wide longitudinal grooves ensure excellent effective water evacuation and improve aquaplaning.



The lateral continuous pattern block, reduces the heat in high speed, ensures the stability at cornering and brings precise driving experience.



The streamlined pattern shape inside, efficiently water-evacuating and high performance of wet ground.



Special compound design with low heat generation, and high grip performance provides super dry and wet handling.

Series	Size	Load Index	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Max. Pressure	
					mm	mm	kg	lbs	kPa	psi
70	235/70R16	106	H	7.0	240	736	950	2094	300	44
	245/70R16	107	H	7.0	248	750	975	2149	300	44
	265/70R16	112	H	8.0	272	778	1120	2469	300	44
65	225/65R17	102	H	6.5	228	724	850	1874	300	44
	235/65R17	108 XL	HV	7.0	240	738	1000	2205	340	50
	245/65R17	107	H	7.0	248	750	975	2150	300	44
	255/65R17	110	H	7.5	260	764	1060	2337	300	44
	265/65R17	112	H	8.0	272	776	1120	2469	300	44
60	215/60R17	96	H	6.5	221	690	710	1565	300	44
	235/60R18	107 XL	VW	7.0	240	739	975	2149	340	50
	255/60R17	106	HV	7.5	260	738	950	2094	300	44
45	235/55R17	103 XL	VW	7.5	245	690	875	1929	340	50
	235/55R19	105 XL	VW	7.5	245	741	925	2039	340	50
	255/55R18	109 XL	VW	8.0	265	737	1030	2271	340	50
	275/55R17	109	V	8.5	284	734	1030	2271	300	44
	285/55R18	113	V	9.0	297	771	1150	2535	300	44
50	255/50R20	109 XL	VW	8.0	265	764	1030	2271	340	50
	265/50R20	111 XL	VW	8.5	277	775	1090	2403	340	50
	275/50R20	113 XL	VW	8.5	284	784	1150	2535	340	50
45	275/45R20	110 XL	VW	9.0	273	756	1060	2337	340	50
	295/45R19	109	W/Y	10.0	296	739	1030	2271	300	44
40	275/40R20	106 XL	W/Y	9.5	278	728	950	2094	340	50
	295/40R20	110 XL	W/Y	10.5	301	744	1060	2237	340	50
35	255/35R19	96 XL	W	9.0	260	661	710	1565	340	50




CATCHFORS A/T -P



Four main non-straight grooves and wild lateral block provide strong cross-country performance that deal with all kinds of road easily.



Three-dimensional pattern design to protect pattern block in severe road.



Jointless wrapping nylon, two layers of high-tension steel belts, dimensional stability polyester carcass consist the strong tire body, transfer the strong power.




Particular tread compounds with big pattern blocks and proper sea/land ratio to ensure steady directional stability in all-surface traction and all-weather condition.

Size	Size	Load Index	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Max. Pressure	
					mm	mm	kg	lbs	kPa	psi
65	P215/65R16	96	T/H	6.5	221	686	710	1565	300	44
	P225/65R17	100	T/H	6.5	228	724	800	1764	300	44
	P235/65R17	103	T/H	7.0	240	738	875	1929	300	44
	P245/65R17	105	T/H	7.0	248	750	925	2039	300	44
	P265/65R17	110	T	8.0	272	776	1060	2337	300	44
70	P215/70R16	99	H	6.5	221	708	775	1709	300	44
	P225/70R16	101	T	6.5	228	722	825	1819	300	44
	P235/70R16	104	T	7.0	240	736	900	1984	300	44
	P245/70R16	106	S	7.0	248	750	950	2094	300	44
	P245/70R17	108	S	7.0	248	776	1000	2205	300	44
	P255/70R16	109/112	S	7.5	260	764	1030	2271	300	44
	P265/70R16	111	T	8.0	272	778	1090	2403	300	44
	P265/70R17	113	T	8.0	272	804	1150	2535	300	44
	P275/70R16	114	S	8.0	279	792	1180	2601	300	44
75	P235/75R15	105	S	6.5	235	733	920	2028	300	44
	P245/75R16	109	S	7.0	248	774	1030	2271	300	44




CATCHFORS A/T -LT



Four main non-straight grooves and wild lateral block provide strong cross-country performance that deal with all kinds of road easily.



Three-dimensional pattern design to protect pattern block in severe road.



Jointless wrapping nylon, two layers of high-tension steel belts, dimensional stability polyester carcass consist the strong tire body, transfer the strong power.



Particular tread compounds with big pattern blocks and proper sea/land ratio to ensure steady directional stability in all-surface traction and all-weather condition.

Series	Size	Load Index	Ply Rating	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Pressure	
						mm	mm	kg	lbs	kPa	psi
85	31x10.50R15LT	109	C / 6PR	S	8.5	268	775	1030	3042	350	51
	LT215/85R16	115/112	E / 10PR	S	6.0	216	772	1215/1120	2680/2470	550	80
	LT235/85R16	120/116	E / 10PR	S	6.5	235	806	1380/1260	3040/2780	550	80
	LT225/75R16	115/112	E / 10PR	S	6.0	223	744	1215/1120	2680/2470	550	80
75	LT235/75R15	104/101	C / 6PR	S	6.5	235	733	900/825	1985/1820	350	51
	LT245/75R16	120/116	E / 10PR	S	7.0	248	774	1380/1260	3040/2780	550	80
	LT265/75R16	123/120	E / 10PR	R	7.5	267	804	1550/1400	3415/3085	550	80
	LT285/75R16	122/119	D / 8PR	R	8.0	286	834	1500/1360	3305/3000	450	65
70	LT265/70R17	121/118	E / 10PR	R	8.0	272	804	1450/1320	3195/2910	550	80




Primetour



Four main grooves provide good driving stability and wet performance.



Special tread compound, ensure the tire performance stability in all kinds of weather conditions.



Reasonable pattern area, perfect collocation of every grooves.



White sidewall rib shows extraordinary appearance.


Series	Size	Load Index	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Max. Pressure	
					mm	mm	kg	lbs	kPa	psi
75	P185/75R14	89	S/T	5.0	184	634	585	1290	300	44
	P195/75R14	92	S/T	5.0	196	648	635	1400	300	44
	P205/75R14	95	S/T	5.5	203	664	695	1532	300	44
	P205/75R15	97	S/T	5.5	203	689	725	1598	300	44
	P215/75R15	100	S/T	6.0	216	703	790	1742	300	44
	P225/75R15	102	S/T	6.0	223	719	850	1874	300	44
	P235/75R15	105	S/T	6.5	235	733	920	2028	300	44




PASSIONCONTACT




Super wide road-contacted tread provide high-speed stability, precise drivability, better drive and brake.



The precise asymmetrical pattern design ensure comfortable and quiet in high speed.




Dual steel belt with high modulus, reinforces stiffness of tread, high strength bead wire, provides super handling performance.



Low rolling resistance, heat dissipation tread compound.

Series	Size	Load Index	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Max. Pressure	
					mm	mm	kg	lbs	kPa	psi
30	265/30ZR19	93 XL	W	9.5	271	643	650	1433	340	50
	275/30ZR20	97 XL	W/Y	9.5	278	674	730	1609	340	50
35	225/35R19	88 XL	W	8.0	240	641	560	1235	340	50
	245/35R19	93 XL	W	8.5	248	750	650	1433	340	50
	255/35R18	94 XL	W/Y	9.0	260	635	670	1477	340	50
40	225/40R18	92 XL	W	8.0	230	637	630	1389	340	50

MILE MAX



Super structure and special profile provide high load capacity and comfortable.



Perfect location of main grooves and lateral grooves, take the good balance with driving stability and traction performance.



Continuous tire shoulder pattern block with special sipe suppress unnorm wear effectively.



High mileage compound.

Series	Size	Load Index	Ply Rating	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Pressure	
						mm	mm	kg	lbs	kPa	psi
85	185R14C	102/100	D / 8PR	R	5.5	188	650	850/800	1875/1765	450	65
	185R15C	103/102	D / 8PR	R	5.5	188	674	875/850	1930/1875	450	65
	195R14C	106/104	D / 8PR	R	5.5	198	666	950/900	2095/1985	450	65
	195R15C	106/104	D / 8PR	R	5.5	198	693	950/900	2095/1985	450	65
75	185/75R16C	104/102	D / 8PR	R	5.0	184	684	900/850	1985/1875	475	69
	195/75R16C	107/105	D / 8PR	R	5.5	196	698	975/925	2150/2040	475	69
	205/75R16C	110/108	D / 8PR	R	5.5	203	714	1060/1000	2335/2205	475	69
	215/75R16C	113/111	D / 8PR	R	6.0	216	728	1150/1090	2535/2405	475	69
70	195/70R15C	104/102	D / 8PR	R	6.0	201	655	900/850	1985/1875	450	65
	205/70R15C	106/104	D / 8PR	R	6.0	209	669	950/900	2095/1985	450	65
	215/70R15C	109/107	D / 8PR	R	6.5	221	683	1030/975	2270/2150	450	65
	225/70R15C	112/110	D / 8PR	R	6.5	228	697	1120/1060	2470/2335	450	65
65	195/65R16C	100/98	C / 6PR	R	6.0	201	660	800/750	1765/1655	375	55
	225/65R16C	112/110	D / 8PR	R	6.5	228	698	1120/1060	2470/2335	475	69
	235/65R16C	115/113	D / 8PR	R	7.0	240	712	1215/1150	2680/2535	475	69



WINTER120



Winter



Safety



Comfort



Economy




Silence



Special compound design, can still keep the tread soft and elastic when contact with snow road in low temperature.



Pattern shape instantly remove water film on the surface of the tire.



Beautiful leaf form and streamline directional pattern shape, throw the snow which in grooves high efficiency.



Special profile for winter tire ensures the stability of the driving on snow road.

Series	Size	Load Index	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Max. Pressure	
					mm	mm	kg	lbs	kPa	psi
65	175/65R14	82	T/H	5.0	177	584	475	1047	300	44
	185/65R14	86	T/H	5.5	189	596	530	1168	300	44
	195/65R15	91	T/H	6.0	201	635	615	1356	300	44
	205/65R15	94	T/H	6.0	209	627	670	1477	300	44
	215/65R15	96	T/H	6.5	221	662	710	1565	300	44
60	185/60R14	82	T/H	5.5	189	578	475	1047	300	44
	185/60R15	84	T/H	5.5	189	603	500	1102	300	44
	195/60R14	86	T/H	6.0	201	590	530	1168	300	44
	195/60R15	88	T/H	6.0	201	615	560	1235	300	44
	205/60R15	91	T/H	6.0	209	627	615	1356	300	44
	205/60R16	92	T/H	6.0	209	652	630	1389	300	44
	215/60R15	94	T/H	6.5	221	639	670	1477	300	44
	215/60R16	95	T/H	6.5	221	664	690	1521	300	44
	225/60R16	98	T/H	6.5	228	676	750	1653	300	44
	235/60R16	100	T/H	7.0	240	688	800	1764	300	44
55	185/55R14	80	T/H	6.0	194	560	450	992	300	44
	185/55R15	82	T/H	6.0	194	585	475	1047	300	44
	195/55R15	85	T/H	6.0	201	595	515	1135	300	44
	195/55R16	87	T/H	6.0	201	620	545	1201	300	44
	205/55R16	91	T/H	6.5	214	632	615	1356	300	44
	215/55R16	93	T/H	7.0	226	642	650	1433	300	44



ICE-CROWN



Special compound design, can still keep the tread soft and elastic when contact with snow road in low temperature.



Pattern shape instantly removes water film on the surface of the tire.



Beautiful leaf form and streamline directional pattern shape, throw the snow which in grooves high efficiency.



Special profile for winter tire ensures the stability of the driving on snow road.

Series	Size	Load Index	Speed Rating	Standard Rim	Section Width	Overall Diameter	Max. Load		Max. Pressure	
					mm	mm	kg	lbs	kPa	psi
65	225/65R17	102	T	6.5	228	724	850	1874	300	44
	235/65R17	108	H	7.0	240	738	1000	2205	340	50
	245/65R17	107	H	7.0	248	750	975	2149	300	44
70	235/70R16	106	T	7.0	240	736	950	2094	300	44
	245/70R16	107	S	7.0	248	750	975	2149	300	44
	245/70R17	110	S	7.0	248	776	1060	2337	300	44
75	235/75R15	105	S	6.5	235	733	925	2039	300	44
	245/75R16	111	S	7.0	248	774	1090	2403	300	44

Brands & Tire Ratings

Brand	PCR	Winter	TBR	OTR	MC
Hao Hua	A	A			
Beijing Capital Tyres	A	A			NO
Wanli	A	A			NO
Farroad	A	NO	NO	NO	NO
Sportrak	B	NO	B	NO	NO
Three A	A	A	A	A	NO
Jinyu	A	A	A	NO	NO
Boto/Wanda	A	A	A	NO	NO
Wosen	NO	NO	B	B	NO
Huasheng	NO	NO	A	A	B
A – Top rated	B- Next Top rated	NO – Not made by the vendor	MC – Motorcycle Tire		