

TIRE CATALOG

2014-2015

[II]

Comforser

Driving Comfort

Comforser

Driving Comfort

SN TIRE

SHANDONG NEW CONTINENT TIRE CO., LTD

Add: Yishui, Shandong, China

www.comforser.com

Authorized Distributor:

SN TIRE

SHANDONG NEW CONTINENT TIRE CO., LTD

(Member of YINBAO TYRE Group)



As one of the member of Yinbao Tire Group,
 the SNC tire factory has been opened with
 the most modern and experienced tire technologies:

- _ Factory Opened: November, 2013
- _ Brand Name: **Comforser**
- _ Trading Logo: **Comforser**
- _ Factory Location: Yishui, Shandong, China
- _ Production Capacity: 6M/Y

We can supply what you want.

We may missing your important sizes, if so
 let us know, we can add in our production line.
 You will be our good partner, why don't you
 add our **Comforser** brand tire in your business line.

Comforser Line-UP



Available Sizes



CF500	CF600	CF700	CF900	CF300	CF1000	CF2000	CF3000
185/55R15	155/70R13	205/45ZR17	185/65R14	WS/BS 185R14C 8PR	OWL P215/75R15	215/75R15	LT215/85R16
195/55R15	165/70R13	215/45ZR17	185/65R15	WS/BS 195R14C 8PR	OWL P235/75R15	225/75R15	LT235/85R16
195/55R16	165/70R14	225/45ZR17	195/65R15	WS/BS 195R15C 8PR	OWL P215/70R16	235/75R15	OWL LT215/75R15
205/55R15	175/70R13	235/45ZR17	205/65R15	BS 185/75R16C 8PR	OWL P235/70R16	205/70R14	LT225/75R16
205/55R16	175/70R14	245/45ZR18	215/65R16	BS 195/75R16C 8PR	OWL P245/70R16	205/70R15	OWL LT235/75R15
205/55R17	185/70R14	245/45ZR19	205/55R16	WS 205/75R14C 8PR	OWL P265/70R16	215/70R16	LT245/75R16
215/55R16	195/70R14	205/40ZR17		WS 205/75R15C 8PR	OWL P265/65R17	225/70R16	OWL LT265/75R16
215/55R17	215/70R15	215/40ZR17		BS 195/70R15C 8PR	OWL LT235/85R16	235/70R16	OWL LT285/75R16
225/55R16	175/65R14	225/40ZR18		WS 205/70R15C 8PR	OWL LT245/75R16	245/70R16	OWL LT315/75R16
225/55R17	175/65R15	235/40ZR18		BS 225/70R15C 8PR	OWL LT265/75R16	255/70R16	LT265/70R17
235/55R17	185/65R14	245/40ZR20		BS 195/65R16C 8PR	OWL LT265/70R17	265/70R16	LT285/70R17
185/50R16	185/65R15	255/40ZR19		BS 205/65R16C 8PR	OWL 265/70R16LT	275/70R16	OWL LT305/70R16
195/50R15	195/65R15	275/40ZR19		BS 215/65R16C 8PR	OWL 285/70R17LT	205/65R16	OWL 31×10.50R15LT
195/50R16	205/65R15	235/35ZR19		BS 225/65R16C 8PR	OWL 285/75R16LT	215/65R16	OWL 32×11.50R15LT
205/50R15	215/65R15	245/35ZR20		BS 235/65R16C 8PR	OWL 30×9.50R15LT	225/65R17	OWL 33×12.50R15LT
205/50R16	185/60R14	275/35ZR20			OWL 31×10.50R15LT	235/65R17	OWL 33×12.50R17LT
205/50R17	185/60R15	※ 205/45ZR18			OWL 35×12.50R17LT	245/65R17	OWL 33×12.50R18LT
215/50R17	195/60R15	※ 215/40ZR16			OWL 35×12.50R18LT	255/65R17	OWL 33×12.50R20LT
225/50R16	195/60R16	※ 245/40ZR17			OWL 35×12.50R20LT	265/65R17	OWL 35×12.50R17LT
225/50R17	205/60R15	※ 215/35ZR18				275/65R17	OWL 35×12.50R18LT
	205/60R16	※ 265/35ZR18				285/65R17	OWL 35×12.50R20LT
	215/60R15	※ 265/30ZR19				225/60R17	OWL 35×13.50R20LT
	215/60R16					235/60R18	
	225/60R15					275/60R20	
	225/60R16					LT245/70R17	
	235/60R16					LT265/70R17	
20 Sizes	26 Sizes	22 Sizes	6 Sizes	15 Sizes	19 Sizes	27 Sizes	22 Sizes
Detailed Page:6-7	Page:8-9	Page:4-5	Page:16-17	Page:18-19	Page:10-11	Page:12-13	Page:14-15

Note: ※ : Under developing.

WS/BS: Both white sidewall and black sidewall available.

WS: Only white sidewall available.

BS: Only black sidewall available.

OWL: Outlined white letter.

CF700



UHP tire Comforser flag-ship tire UTQG 380 A A



Features and Benefits

Asymmetric tread design
Inside for good water drainage.
Outside for good riding stability
and precise handling.

Inside

**4 circumferential
straight grooves**
for excellent water drainage
and minimizes risk of
aquaplaning at high speed.

Outside

Various siping
on the tread and variable
pitch on the shoulder blocks
minimize noise level.

Silica tread compound
for lower rolling resistance
and excellent road holding.



Sizes	LI/SS	Std/XL	MFS	Rim	Dimensions			Max. Load (kg)	Max. Press. (kPa)	UTQG
					OD	SW	NSD			
205/45ZR17	88W	XL	Yes	7.0	616	206	8.2	560	350	380 A A
215/45ZR17	91W	XL	Yes	7.0	626	213	8.2	615	350	380 A A
225/45ZR17	94W	XL	Yes	7.5	634	225	8.5	670	350	380 A A
235/45ZR17	97W	XL	Yes	8.0	644	236	8.5	730	350	380 A A
245/45ZR18	100W	XL	Yes	8.0	677	243	8.5	800	350	380 A A
245/45ZR19	102W	XL	Yes	8.0	703	243	8.5	850	350	380 A A
205/40ZR17	84W	XL	Yes	7.5	596	212	8.5	500	350	380 A A
215/40ZR17	87W	XL	Yes	7.5	604	218	8.5	545	350	380 A A
225/40ZR18	92W	XL	Yes	8.0	637	230	8.5	630	350	380 A A
235/40ZR18	95W	XL	Yes	8.5	645	241	8.5	690	350	380 A A
245/40ZR20	99W	XL	Yes	8.5	704	248	8.5	775	350	380 A A
255/40ZR19	100W	XL	Yes	9.0	687	260	8.5	800	350	380 A A
275/40ZR19	105W	XL	Yes	9.5	703	278	8.5	925	350	380 A A
235/35ZR19	91W	XL	Yes	8.5	647	241	8.5	615	350	380 A A
245/35ZR20	95W	XL	Yes	8.5	680	248	8.5	690	350	380 A A
275/35ZR20	102W	XL	Yes	9.5	700	278	8.5	850	350	380 A A
※ 205/45ZR16	87W	XL	Yes	7.0	590	206	8.0	545	350	380 A A
※ 215/40ZR18	89W	XL	Yes	7.5	629	218	8.5	580	350	380 A A
※ 245/40ZR17	95W	XL	Yes	8.5	628	248	8.5	690	350	380 A A
※ 215/35ZR18	84W	XL	Yes	7.5	607	218	8.5	500	350	380 A A
※ 265/35ZR18	97W	XL	Yes	9.5	643	271	8.5	730	350	380 A A
※ 265/30ZR19	93W	XL	Yes	9.5	643	271	8.6	650	350	380 A A

※ : Under developing.

MFS: Max Flange Shield.

XL: Extra Load (Reinforced)

CF500



High performance tire covering 55/50 series UTQG 380 A A



Features and Benefits

Aggressive uni-directional tread design

for excellent water evacuation and reduces aquaplaning at high speed.



Variable pitch

combination on the shoulder blocks and siping on the tread surface for quiet riding.



Solved irregular wear
newly developed directional tread design solved irregular wear.

Silica tread compound
for lower rolling resistance and excellent road holding.

Sizes	LI/SS	Std/XL	MFS	Rim	Dimensions			Max. Load (kg)	Max. Press (kPa)	UTQG
					OD	SW	NSD			
185/55R15	82V	Std	Yes	6.0	585	194	8.2	475	350	380 A A
195/55R15	85V	Std	Yes	6.0	595	201	8.2	515	350	380 A A
195/55R16	87V	Std	Yes	6.0	620	201	8.2	545	350	380 A A
205/55R15	88V	Std	Yes	6.5	607	214	8.2	560	350	380 A A
205/55R16	94W	XL	Yes	6.5	632	214	8.2	670	350	380 A A
205/55R17	95W	XL	Yes	6.5	658	214	8.2	690	350	380 A A
215/55R16	97W	XL	Yes	7.0	642	226	8.2	730	350	380 A A
215/55R17	98W	XL	Yes	7.0	668	226	8.2	750	350	380 A A
225/55R16	99W	XL	Yes	7.0	654	233	8.2	775	350	380 A A
225/55R17	101W	XL	Yes	7.0	680	233	8.2	825	350	380 A A
235/55R17	103W	XL	Yes	7.5	690	245	8.2	875	350	380 A A
185/50R16	81V	Std	Yes	6.0	592	194	8.0	462	350	380 A A
195/50R15	82V	Std	Yes	6.0	577	201	8.0	475	350	380 A A
195/50R16	84V	Std	Yes	6.0	602	201	8.0	500	350	380 A A
205/50R15	86V	Std	Yes	6.5	587	214	8.0	530	350	380 A A
205/50R16	87W	Std	Yes	6.5	612	214	8.2	545	350	380 A A
205/50R17	93W	XL	Yes	6.5	638	214	8.2	650	350	380 A A
215/50R17	95W	XL	Yes	7.0	648	226	8.2	690	350	380 A A
225/50R16	92W	Std	Yes	7.0	632	233	8.2	630	350	380 A A
225/50R17	98W	XL	Yes	7.0	658	233	8.2	750	350	380 A A

UTQG: Will change to 440 A A in Q1 2015.

CF600



High performance tire covering 70/65/60 series UTQG 380 A A



Features and Benefits

Aggressive uni-directional tread design

for excellent water evacuation and reduces aquaplaning at high speed.



Variable pitch

combination on the shoulder blocks and sipes on the tread surface for quiet riding.



Solved irregular wear
newly developed directional tread design solved irregular wear.

Silica tread compound
for lower rolling resistance and excellent road holding.

Sizes	LI/SS	Std/XL	Rim	Dimensions			Max. Load (kg)	Max. Press (kPa)	UTQG
				OD	SW	NSD			
155/70R13	75T	Std	4.5	548	157	7.8	387	300	380 A A
165/70R13	79T	Std	5.0	562	170	7.8	437	300	380 A A
165/70R14	81H	Std	5.0	588	170	7.8	462	300	380 A A
175/70R13	82H	Std	5.0	576	177	7.8	475	300	380 A A
175/70R14	84H	Std	5.0	602	177	7.8	500	300	380 A A
185/70R14	88H	Std	5.5	616	189	8.0	560	300	380 A A
195/70R14	91H	Std	6.0	630	201	8.0	615	300	380 A A
215/70R15	98H	Std	6.5	683	221	8.2	750	300	380 A A
175/65R14	82H	Std	5.0	584	177	7.8	475	300	380 A A
175/65R15	84H	Std	5.0	609	177	7.8	500	300	380 A A
185/65R14	88H	Std	5.5	596	189	8.2	530	300	380 A A
185/65R15	88H	Std	5.5	621	189	8.2	560	300	380 A A
195/65R15	91H	Std	6.0	635	201	8.2	615	300	380 A A
205/65R15	94H	Std	6.0	647	209	8.2	670	300	380 A A
215/65R15	98H	Std	6.5	661	221	8.2	710	300	380 A A
185/60R14	82H	Std	5.5	578	189	8.2	475	300	380 A A
185/60R15	84H	Std	5.5	603	189	8.2	500	300	380 A A
195/60R15	88H	Std	6.0	615	201	8.2	560	300	380 A A
195/60R16	89H	Std	6.0	640	201	8.2	580	300	380 A A
205/60R15	91H	Std	6.0	627	209	8.2	615	300	380 A A
205/60R16	92H	Std	6.0	652	209	8.2	630	300	380 A A
215/60R15	94H	Std	6.5	639	221	8.2	670	300	380 A A
215/60R16	95H	Std	6.5	664	221	8.2	690	300	380 A A
225/60R15	96V	Std	6.5	651	228	8.2	710	350	380 A A
225/60R16	98V	Std	6.5	676	228	8.2	750	350	380 A A
235/60R16	100H	Std	7.0	688	240	8.2	800	350	380 A A

UTQG: Will change to 440 A A in Q1 2015.

CF1000 AT



A/T SUV OWL (Outlined White Letter)

Comforser
Driving Comfort

Features and Benefits

Designed and built for all terrain use

on road driving considered high speed stability, off road driving, and strong traction. Given tough tread block.

Adopted special tread compound

for long mileage and less fuel consumption.



Numerous sipes

on the block for improved traction in winter conditions and wet road conditions. Also they contribute to minimize noise level.

Sidewall	Sizes	LI/SS	PR	Rim	Dimensions			Max. Load (kg)		Max. Press (kPa)	UTQG
					OD	SW	NSD	Single	Dual		
OWL	P215/75R15	102S/100S	—	6.0	703	216	10.5	790	—	300	420 AA
OWL	P235/75R15	108S	—	6.5	733	235	10.8	920	—	300	420 AA
OWL	P215/70R16	99T	—	6.5	708	221	10.5	775	—	300	420 AA
OWL	P235/70R16	104T	—	7.0	736	240	10.8	900	—	300	420 AA
OWL	P245/70R16	106S	—	7.0	750	248	10.8	950	—	300	420 AA
OWL	P265/70R16	111T	—	8.0	778	272	10.8	1090	—	300	420 AA
OWL	P265/65R17	110T	—	8.0	776	272	10.8	1090	—	300	420 AA
OWL	LT235/85R16	120/116S	10	6.5	806	235	13.0	1380	1260	550	—
OWL	LT245/75R16	120/116S	10	7.0	774	248	13.0	1380	1260	550	—
OWL	LT265/75R16	123/120S	10	7.5	804	267	13.0	1550	1400	550	—
OWL	LT265/70R17	121/118S	10	8.0	804	272	13.0	1450	1320	550	—
OWL	265/70R16LT	121/118S	10	8.0	778	272	13.0	1450	1320	550	—
OWL	285/70R17LT	121/118S	10	8.5	832	292	13.0	1450	1320	550	—
OWL	285/75R16LT	126/123S	10	8.0	834	286	13.0	1700	1550	550	—
OWL	30×9.50R15LT	104R	6	7.5	750	240	13.0	900	—	350	—
OWL	31×10.50R15LT	109S	6	8.5	775	268	13.0	1030	—	350	—
OWL	35×12.50R17LT	121S	10	10.0	877	318	13.0	1450	—	450	—
OWL	35×12.50R18LT	123S	10	10.0	877	318	13.0	1550	—	450	—
OWL	35×12.50R20LT	121S	10	10.0	877	318	13.0	1450	—	450	—

OWL: Outlined white letter.

CF2000 HT



H/T SUV

Comforser
Driving Comfort

Features and Benefits

Designed for paved road use.

Zigzag sipes on the shoulder blocks and thousand of sipes on the tread are for reducing noise level and improved traction in both wet and dry conditions.



4 circumferential grooves for excellent water evacuation for good wet traction.

Wider center rib for stable handling at high speed straight line driving.

Sizes	LI/SS	Rim	Dimensions			Max. Load (kg)	Max. Press (kPa)	UTQG
			OD	SW	NSD			
215/75R15	100H	6.0	703	216	8.5	800	300	420 AA
225/75R15	102H	6.0	719	223	8.5	850	300	420 AA
235/75R15	105H	6.5	733	235	8.5	925	300	420 AA
205/70R14	95H	6.0	644	209	8.5	690	300	420 AA
205/70R15	96H	6.0	669	209	8.5	710	300	420 AA
215/70R16	100H	6.5	708	221	8.5	800	300	420 AA
225/70R16	103H	6.5	722	228	8.5	875	300	420 AA
235/70R16	106H	7.0	736	240	8.5	950	300	420 AA
245/70R16	107H	7.0	750	248	8.5	975	300	420 AA
255/70R16	111H	7.5	764	260	8.8	1090	300	420 AA
265/70R16	112H/T	8.0	778	272	8.8	1120	300	420 AA
275/70R16	114H/T	8.0	792	279	8.8	1180	300	420 AA
205/65R16	95H	6.0	672	209	8.5	690	300	420 AA
215/65R16	102H	6.5	686	221	8.5	850	340	420 AA
225/65R17	102H	6.5	724	228	8.5	850	300	420 AA
235/65R17	108H	7.0	738	240	8.5	1000	340	420 AA
245/65R17	107H	7.0	750	248	8.5	975	300	420 AA
255/65R17	110H	7.5	764	260	8.8	1060	300	420 AA
265/65R17	112H	8.0	776	272	8.8	1120	300	420 AA
275/65R17	119H	8.0	790	279	8.8	1360	340	420 AA
275/65R18	116T/H	8.0	815	279	8.8	1250	300	420 AA
285/65R17	116H	8.5	802	292	8.8	1250	300	420 AA
225/60R17	103H	6.5	702	228	8.5	875	340	420 AA
235/60R18	107H	7.0	739	240	8.5	975	340	420 AA
275/60R20	115H	8.0	838	279	8.8	1215	300	420 AA
LT245/70R17 10PR	119/116S	7.0	776	248	10.8	1360/1250	550	—
LT265/70R17 10PR	121/118S	8.0	804	272	10.8	1450/1320	550	—

CF3000 MT



M/T SUV OWL (Outlined White Letter)

Features and Benefits



Sidewall	Sizes	LI/SS	PR	Rim	Dimensions			Max. Load (kg)		Max. Press (kPa)
					OD	SW	NSD	Single	Dual	
	LT215/85R16	115/112Q	10	6.0	778	216	14.0	1215	1120	550
	LT235/85R16	120/116Q	10	6.5	812	235	15.0	1380	1260	550
OWL	LT215/75R15	100/97Q	6	6.0	709	216	14.0	800	730	350
	LT225/75R16	115/112Q	10	6.0	750	223	14.0	1215	1120	550
OWL	LT235/75R15	104/101Q	6	6.5	739	235	14.0	900	825	350
	LT245/75R16	120/116Q	10	7.0	780	248	15.0	1380	1260	550
OWL	LT265/75R16	123/120Q	10	7.5	810	267	15.0	1550	1400	550
OWL	LT285/75R16	126/123Q	10	8.0	840	286	15.0	1700	1550	550
OWL	LT315/75R16	127/124Q	10	8.5	884	313	15.0	1750	1600	450
	LT265/70R17	121/118Q	10	8.0	810	272	15.0	1450	1320	550
	LT285/70R17	121/118Q	8	8.5	838	292	15.0	1450	1320	450
	LT305/70R16	118/115Q	8	9.0	840	311	15.0	1320	1215	350
OWL	31×10.50R15LT	109Q	6	8.5	781	268	15.0	1030	—	350
OWL	32×11.50R15LT	113Q	6	9.0	807	290	15.0	1150	—	350
OWL	33×12.50R15LT	108Q	6	10.0	832	318	15.0	1000	—	250
OWL	33×12.50R17LT	114Q	8	10.0	832	318	15.0	1180	—	350
OWL	33×12.50R18LT	118Q	10	10.0	832	318	15.0	1320	—	450
OWL	33×12.50R20LT	114Q	10	10.0	832	318	15.0	1180	—	450
OWL	35×12.50R17LT	121Q	10	10.0	883	318	16.0	1450	—	450
OWL	35×12.50R18LT	123Q	10	10.0	883	318	16.0	1550	—	450
OWL	35×12.50R20LT	121Q	10	10.0	883	318	16.0	1450	—	450
OWL	35×13.50R20LT	124Q	10	10.0	883	345	16.0	1600	—	450

OWL: Outlined white letter.

CF900



Studless Winter



Features and Benefits

Directional tread design provides excellent gripping power on icy or snowy roads and provides good adhesion with the road surface.

Special silica tread compound provides good traction on icy or snowy roads.



Thousand of zigzag sipes and checkers lines on the tread catch road surface of icy or snowy and provide good adhesion with the road surface.



Sizes	LI/SS	Std/XL	Rim	Dimensions			Max. Load (kg)	Max. Press (kPa)
				OD	SW	NSD		
185/65R14	86T	Std	5.5	596	189	9.3	530	300
185/65R15	88H	Std	5.5	621	189	9.3	560	300
195/65R15	95T	XL	6.0	635	201	9.3	690	300
205/65R15	94H	Std	6.0	647	209	9.3	670	300
215/65R16	98H	Std	6.5	686	221	9.3	750	300
205/55R16	91H	Std	6.5	644	220	9.3	615	300

CF300



Commercial vehicle tire

Features and Benefits

Wider tread
for more mileage
and stable handling.

Stone ejectors
in main shoulder grooves
for minimizing casing
damage.



Sipes
on the center ribs and
shoulder ribs provide
excellent gripping on
both dry and wet road
conditions.

Shoulder protectors
protect tire damage
from curb stone.



Sidewall	Sizes	LI/SS	Rim	Dimensions			Max. Load (kg)		Max. Press (kPa)
				OD	SW	NSD	Single	Dual	
WS/BS	185R14C 8PR	102/100Q	5.5	650	188	10.8	850	800	450
WS/BS	195R14C 8PR	106/104Q	5.5	666	198	10.8	950	900	450
WS/BS	195R15C 8PR	106/104R	5.5	693	196	10.8	950	900	450
BS	185/75R16C 8PR	107/105R	5.0	684	184	9.3	900	850	475
BS	195/75R16C 8PR	107/105R	5.5	698	196	10.3	975	925	475
WS	205/75R14C 8PR	109/107R	5.5	664	203	10.3	1030	975	475
WS	205/75R15C 8PR	110/108R	5.5	689	203	10.3	1060	1000	475
BS	195/70R15C 8PR	104/102R	6.0	655	201	10.3	900	850	450
WS	205/70R15C 8PR	106/104R	6.0	669	209	10.3	950	900	450
BS	225/70R15C 8PR	112/110R	6.5	697	228	10.3	1120	1060	450
BS	195/65R16C 8PR	104/102R	6.0	660	201	10.3	900	850	475
BS	205/65R16C 8PR	107/105T	6.0	672	209	10.3	975	925	475
BS	215/65R16C 8PR	109/107T	6.5	686	221	10.3	1030	975	475
BS	225/65R16C 8PR	112/110T	6.5	698	228	10.3	1120	1060	475
BS	235/65R16C 8PR	115/113T	7.0	712	240	10.3	1215	1150	475

WS/BS: Both white sidewall and black sidewall available.

WS: Only white sidewall available.

BS: Only black sidewall available.

**All Tire Made by Yinbao Group
is Insured by CPIC**

MEMO



太平洋保險
CPIC

中国太平洋财产保险股份有限公司
China Pacific Property Insurance Co., Ltd.

产品责任保险承保证明

山东银宝轮胎集团有限公司连续六年在我公司投保产品责任保险, 保险期间山东银宝轮胎集团有限公司从未出现产品质量事故索赔, 2014 年我公司继续为山东银宝轮胎集团有限公司承保出口及内销产品责任保险。

注：1、承保条件以正式保单约定为准。

2. 本说明不得以任何形式作为产品宣传材料。

中国太平洋财产保险股份有限公司

濟南中心支公司

2014年8月1日